



Essential SmartBright G4 LED Floodlight BVP150

BVP150 LED63/NW PSU 70W SWB G2 GM

Essential SmartBright G4 LED Floodlight BVP150 - 6650 lm - 70 W - 4000 K

The Essential SmartBright G4 LED floodlight comes in a compact and sturdy design. Lightweight, with a robust die-cast aluminum housing and corrosion-proof coating, it's suitable for general outdoor applications. Plus, with a higher efficacy than the previous generation, it also saves more energy.

Product data

General information		Power Factor (Min)	
Light source color	840 neutral white		0.9
Driver included	Yes	Controls and dimming	
Optical cover/lens type	Glass	Dimmable	No
Control interface	-	Mechanical and housing	
Connection	Flying leads/wires	Housing Material	Aluminum die-cast
Cable	Cable 0.6 m without plug	Optical cover/lens material	Glass
Protection class IEC	Safety class I	Overall length	276 mm
CE mark	-	Overall width	217 mm
		Overall height	31 mm
Operating and electrical		Effective projected area	0.032 m ²
Input Voltage	220-240 V	Color	Black
Input Frequency	50 or 60 Hz		
Inrush current	1.35 A		

Essential SmartBright G4 LED Floodlight BVP150

Approval and application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]

Initial performance (IEC compliant)

Initial luminous flux (system flux)	6650 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	95 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.380, 0.380) SDCM <6
Initial input power	70 W
Power consumption tolerance	+/-10%

Application conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product data

Full product code	871951453256499
Order product name	BVP150 LED63/NW PSU 70W SWB G2 GM
EAN/UPC - Product	8719514532564
Order code	911401825283
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401825283
Net Weight (Piece)	1.000 kg



Dimensional drawing



	BVP150							
	10W	20W	30W	50W	70W	100W	150W	200W
A	107	141	188	220	273	320	382	454
B	99	122	155	175	212	246	289	331
C	29	27	28	30	33	37	39	40
a	45	75	100	125	125	160	200	210
b	5	5	9	8,5	8,5	8,5	8,5	10,5
c	5,5	5,5	6,5	9	9	9	9	11

BVP150 LED63/NW PSU 70W SWB G2 GM

